

Der Anhänger ist derzeit nicht verfügbar

3-SKS 3100/17 T-AL

Long durability through welded, hot-dip galvanized chassis, plateaus and a loading ramp made of galvanized steel base and 360mm anodised aluminium board walls Stability and resilience thanks to continuous forked drawbar Very versatile Board walls can be folded down and removed in the front, side and back Longevity through strong and highly dimensioned hydraulic components Manual hand pump to tilt backwards Also available as unbraked trailer Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

* Der 3-SKS 3100/17 T-AL ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	3.000 kg
Load capacity	2.139 kg
Self-weight	861 kg
Total length	4.520 mm
Total width	1.945 mm
Total height	1.245 mm
Loading dimensions inside - length	3.075 mm
Loading dimensions inside - width	1.765 mm
Loading dimensions inside - height	360 mm
Sill height	765 mm

FURTHER INFORMATION

description	value
Material type	Aluminium
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	14 inch
Number of lashing points	10
Hydraulic system	Kombipumpe
Hinged front wall	Yes
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chassis, plateaus and a loading ramp made of galvanized steel base and 360mm anodised aluminium board walls Stability and resilience thanks to continuous forked drawbar Very versatile Board walls can be folded down and removed in the front, side and back Longevity through strong and highly dimensioned hydraulic components Manual hand pump to tilt backwards Also available as unbraked trailer Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Vertically adjustable supporting wheel



