3-SKS 3600/17 T



Long durability through welded, hot-dip galvanized chassis, plateaus and a loading ramp made of galvanized steel base and 360mm anodised aluminium board walls Stability and resilience thanks to continous forked drawbar Very versatile Board walls can be folded down and removed in the front, side and back Longevity through strong and highly dimensioned hydraulic components Manual hand pump to tilt backwards Also available as unbraked trailer Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

* Der 3-SKS 3600/17 T ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	3.500 kg
Load capacity	2.460 kg
Self-weight	1.040 kg
Total length	5.020 mm
Total width	1.945 mm
Total height	1.265 mm
Loading dimensions inside - length 3.575 mm	
Loading dimensions inside - width	1.765 mm
Loading dimensions inside - height 400 mm	
Sill height	785 mm

FURTHER INFORMATION

description	value
Material type	steel
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	14 inch
Number of lashing points	10
Hydraulic system	Kombipumpe
Hinged front wall	Yes
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chassis, plateaus and a loading ramp made of galvanized steel base and 360mm anodised aluminium board walls Stability and resilience thanks to continous forked drawbar Very versatile Board walls can be folded down and removed in the front, side and back Longevity through strong and highly dimensioned hydraulic components Manual hand pump to tilt backwards Also available as unbraked trailer Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Vertically adjustable supporting wheel