

Der Anhänger ist derzeit nicht verfügbar

# LPA 230/12 U

Long durability through corrosion-resistant, galvanized steel parts  
Stability and resilience thanks to continuous drawbar  
Compact clamping locks  
Easy storage through positioning on the back due to low self-weight and size  
Very versatile  
Hinged rear panel  
Board walls edged with corner stands  
Easy maintenance and repair on replaceable drawbar, board walls and frame parts  
Slip- and water-resistant base plate provides high resistance and is replaceable  
Numerous accessories to customize the trailer  
Quick and easy setup of accessory through modular plug-in system

\* Der LPA 230/12 U ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

## TECHNICAL DETAILS

description	value
Total weight	750 kg
Load capacity	585 kg
Self-weight	165 kg
Total length	3.405 mm
Total width	1.775 mm
Total height	890 mm
Loading dimensions inside - length	2.245 mm
Loading dimensions inside - width	1.250 mm
Loading dimensions inside - height	360 mm
Sill height	530 mm

## FURTHER INFORMATION

description	value
Material type	steel
brake	unrestrained
Single axle / tandem	Single axle (1 axle)
Tires (inches)	13 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	No

## PRODUCT DESCRIPTION

Long durability through corrosion-resistant, galvanized steel parts  
Stability and resilience thanks to continuous drawbar  
Compact clamping locks  
Easy storage through positioning on the back due to low self-weight and size  
Very versatile  
Hinged rear panel  
Board walls edged with corner stands  
Easy maintenance and repair on replaceable drawbar, board walls and frame parts  
Slip- and water-resistant base plate provides high resistance and is replaceable  
Numerous accessories to customize the trailer  
Quick and easy setup of accessory through modular plug-in system

## STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Two continuous anti-vibration fenders serve as an additional stable base edge
- Elastic-plastic fenders on single axle trailers
- Sturdy-steel fenders on tandem trailers
- Multifunctional luminaires
- Torsion-free chassis
- Depending on the model with 7 or 13-pin light plug
- Supporting wheel on trailers with run up brakes
- Buttons to attach tarpaulins already pre-mounted
- Depending on the model with hinged front wall

