

# LPA 300/15 T

Artikelnummer: 10987

## TECHNICAL DETAILS

description	value
Total weight	2.000 kg
Load capacity	1.599 kg
Self-weight	401 kg
Total length	4.305 mm
Total width	2.025 mm
Total height	890 mm
Loading dimensions inside - length	3.010 mm
Loading dimensions inside - width	1.500 mm
Loading dimensions inside - height	360 mm
Sill height	530 mm

## FURTHER INFORMATION

description	value
Material type	steel
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	No

## PRODUCT DESCRIPTION

Long durability through corrosion-resistant, galvanized steel parts  
 Stability and resilience thanks to continuous drawbar  
 Compact clamping locks  
 Easy storage through positioning on the back due to low self-weight and size  
 Very versatile  
 Hinged rear panel  
 Board walls edged with corner stands  
 Easy maintenance and repair on replaceable drawbar, board walls and frame parts  
 Slip- and water-resistant base plate provides high resistance and is replaceable  
 Numerous accessories to customize the trailer  
 Quick and easy setup of accessory through modular plug-in system

## STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Two continuous anti-vibration fenders serve as an additional stable base edge
- Elastic-plastic fenders on single axle trailers
- Sturdy-steel fenders on tandem trailers
- Multifunctional luminaires
- Torsion-free chassis
- Depending on the model with 7 or 13-pin light plug
- Supporting wheel on trailers with run up brakes
- Buttons to attach tarpaulins already pre-mounted
- Depending on the model with hinged front wall

