

Der Anhänger ist derzeit nicht verfügbar



3-SKS 4100/20 T

Long durability through welded, hot-dip galvanized chassis, loading ramp and 360mm anodised aluminium board walls (Model out of steel: 400mm) Also usable as a platform Very versatile Board walls 4-sided removable the rear panel consists of a pendular platform gate with rungs for increased room while tilting Longevity through strong and highly dimensioned hydraulic components Available with electric or manual hand pump to tilt backwards Possibility to convert various hydraulic components without modification on the trailer Model with rail slots to store the ramps directly in the trailer (ramps as optional accessories) Easy maintenance and repair on replaceable forked drawbar Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

* Der 3-SKS 4100/20 T ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	3.500 kg
Load capacity	2.241 kg
Self-weight	1.259 kg
Total length	5.605 mm
Total width	2.245 mm
Total height	1.265 mm
Loading dimensions inside - length	4.075 mm
Loading dimensions inside - width	2.065 mm
Loading dimensions inside - height	400 mm
Sill height	785 mm

FURTHER INFORMATION

description	value
Material type	steel
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	14 inch
Number of lashing points	10
Hydraulic system	Kombipumpe
Hinged front wall	Yes
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chassis, loading ramp and 360mm anodised aluminium board walls (Model out of steel: 400mm) Also usable as a platform Very versatile Board walls 4-sided removable the rear panel consists of a pendular platform gate with rungs for increased room while tilting Longevity through strong and highly dimensioned hydraulic components Available with electric or manual hand pump to tilt backwards Possibility to convert various hydraulic components without modification on the trailer Model with rail slots to store the ramps directly in the trailer (ramps as optional accessories) Easy maintenance and repair on replaceable forked drawbar Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Vertically adjustable supporting wheel