

Der Anhänger ist derzeit nicht verfügbar



LH 3100/16 G-AL

Long durability through welded, hot-dip galvanized chassis and 300mm anodised aluminium board walls Stability thanks to solid frame construction Aluminium board walls 4-sided hingeable and removable for easier loading and unloading External strong board latches Also usable as a platform Very versatile Easy maintenance and repair on replaceable forked drawbar Slip- and water-resistant base plate provides high resistance and is replaceable Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

* Der LH 3100/16 G-AL ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	1.500 kg
Load capacity	1.152 kg
Self-weight	348 kg
Total length	4.523 mm
Total width	1.726 mm
Total height	945 mm
Loading dimensions inside - length	3.108 mm
Loading dimensions inside - width	1.606 mm
Loading dimensions inside - height	300 mm
Sill height	645 mm

FURTHER INFORMATION

description	value
Material type	Aluminium
brake	decelerated
Single axle / tandem	Single axle (1 axle)
Tires (inches)	13 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	Yes
Tilted	No

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chassis and 300mm anodised aluminium board walls Stability thanks to solid frame construction Aluminium board walls 4-sided hingeable and removable for easier loading and unloading External strong board latches Also usable as a platform Very versatile Easy maintenance and repair on replaceable forked drawbar Slip- and water-resistant base plate provides high resistance and is replaceable Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Elastic-plastic fenders
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Automatic supporting wheel on trailers with run up Brakes

