

RK 2600/15 T-AL

Artikelnummer: 15239

TECHNICAL DETAILS

description	value
Total weight	2.500 kg
Load capacity	1.993 kg
Self-weight	507 kg
Total length	4.026 mm
Total width	1.690 mm
Total height	1.135 mm
Loading dimensions inside - length	2.578 mm
Loading dimensions inside - width	1.510 mm
Loading dimensions inside - height	360 mm
Sill height	645 mm

FURTHER INFORMATION

description	value
Material type	Aluminium
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	4
Hydraulic system	Handpumpe
Hinged front wall	Yes
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chassis, plateaus and a loading ramp made of galvanized steel base and 360mm anodised aluminium board walls. Stability and resilience thanks to continuous forked drawbar. Very versatile. Board walls can be folded down and removed in the front, side and back. Longevity through strong and highly dimensioned hydraulic components. Manual hand pump to tilt backwards. Also available as unbraked trailer. Numerous accessories to customize the trailer. Quick and easy setup of accessory through modular plug-in system.

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Vertically adjustable supporting wheel



Symbolbild