

Der Anhänger ist derzeit nicht verfügbar

MA 250 U-K

Long durability through hot-dip galvanized chassis High stability thanks to bolted frame construction Suitable for the safe transport of one motorcycles Release system with foot control Very versatile Tilttable loading ramp with flat drive-up angle Removable license plate can be used as ramp rail Footboard (base plate) on both sides of the stand ramp for secure loading Easy maintenance and repair on replaceable components

* Der MA 250 U-K ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	750 kg
Load capacity	592 kg
Self-weight	158 kg
Total length	3.288 mm
Total width	1.600 mm
Total height	740 mm
Loading dimensions inside - length	2.480 mm
Loading dimensions inside - width	200 mm
Loading dimensions inside - height	
Sill height	285 mm

FURTHER INFORMATION

description	value
Material type	steel
brake	unrestrained
Single axle / tandem	Single axle (1 axle)
Tires (inches)	13 inch
Number of lashing points	9
Hydraulic system	No
Hinged front wall	No
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through hot-dip galvanized chassis High stability thanks to bolted frame construction Suitable for the safe transport of one motorcycles Release system with foot control Very versatile Tilttable loading ramp with flat drive-up angle Removable license plate can be used as ramp rail Footboard (base plate) on both sides of the stand ramp for secure loading Easy maintenance and repair on replaceable components

STANDARD EQUIPMENT

- 9 tie-rings at the frame for securing the motorcycle
- Maintenance-free rubber spring axle
- Elastic-plastic fenders
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- One stand rail with front wheel bracket
- Supporting wheel

