

LPA 250/13 T-AL

Artikelnummer: 18844

TECHNICAL DETAILS

description	value
Total weight	2.000 kg
Load capacity	1.670 kg
Self-weight	330 kg
Total length	3.825 mm
Total width	1.895 mm
Total height	890 mm
Loading dimensions inside - length	2.510 mm
Loading dimensions inside - width	1.370 mm
Loading dimensions inside - height	360 mm
Sill height	530 mm

FURTHER INFORMATION

description	value
Material type	Aluminium
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	No

PRODUCT DESCRIPTION

Maximum corrosion protection through anodised aluminium board walls. Stability due to an aluminium double frame cavity profile and continuous drawbar Board walls with anchors to stabilize the external side walls Solid board latches Easy storage through positioning on the back due to low self-weight and size (depending on the model) Very versatile Hinged rear panel Easy maintenance and repair on replaceable drawbar, board walls and frame parts Slip- and water-resistant base plate provides high resistance and is replaceable Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Two continuous anti-vibration fenders serve as an additional stable base edge
- Elastic-plastic fenders on single axle trailers
- Sturdy-steel fenders on tandem trailers
- Multifunctional luminaires
- Torsion-free chassis
- Depending on the model 7 or 13-pin light plug
- Supporting wheel on trailers with run up brakes
- Buttons to attach tarpaulins already pre-mounted
- Depending on the model with hinged front wall

