Der Anhänger ist derzeit nicht verfügbar

LPA 206 U-AL-STK

Maximum corrosion protection through anodised aluminium board walls. Stability due to an aluminium double frame cavity profile and continuous drawbar Board walls with anchors to stabilize the external side walls Solid board latches Easy storage through positioning on the back due to low self-weight and size (depending on the model) Very versatile Hinged rear panel Easy maintenance and repair on replaceable drawbar, board walls and frame parts Slip- and water-resistant base plate provides high resistance and is replaceable Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

* Der LPA 206 U-AL-STK ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

| description | value | |
|---|----------|--|
| Total weight | 750 kg | |
| Load capacity | 625 kg | |
| Self-weight | 125 kg | |
| Total length | 3.095 mm | |
| Total width | 1.485 mm | |
| Total height | 890 mm | |
| Loading dimensions inside - length 2.010 mm | | |
| Loading dimensions inside - width | 1.075 mm | |
| Loading dimensions inside - height 360 mm | | |
| Sill height | 530 mm | |

FURTHER INFORMATION

| Material typeAluminiumbrakeunrestrainedSingle axle / tandemSingle axle (1 axle)Tires (inches)13 inchNumber of lashing points8Hydraulic systemNoUinced front wollYan | description | value |
|---|--------------------------|----------------------|
| Single axle / tandemSingle axle (1 axle)Tires (inches)13 inchNumber of lashing points8Hydraulic systemNo | Material type | Aluminium |
| Tires (inches)13 inchNumber of lashing points8Hydraulic systemNo | brake | unrestrained |
| Number of lashing points8Hydraulic systemNo | Single axle / tandem | Single axle (1 axle) |
| Hydraulic system No | Tires (inches) | 13 inch |
| | Number of lashing points | 8 |
| Llinged front well Vec | Hydraulic system | No |
| ningeu iront wait fes | Hinged front wall | Yes |
| Tilted No | Tilted | No |

PRODUCT DESCRIPTION

Maximum corrosion protection through anodised aluminium board walls. Stability due to an aluminium double frame cavity profile and continuous drawbar Board walls with anchors to stabilize the external side walls Solid board latches Easy storage through positioning on the back due to low self-weight and size (depending on the model) Very versatile Hinged rear panel Easy maintenance and repair on replaceable drawbar, board walls and frame parts Slip- and water-resistant base plate provides high resistance and is replaceable Numerous accessories to customize the trailer Quick and easy setup of accessory through modular plug-in system

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Two continuous anti-vibration fenders serve as an additional stable base edge
- Elastic-plastic fenders on single axle trailers
- Sturdy-steel fenders on tandem trailers
- Multifunctional luminaires
- Torsion-free chassis
- Depending on the model 7 or 13-pin light plug
- Supporting wheel on trailers with run up brakes
- Buttons to attach tarpaulins already pre-mounted
- Depending on the model with hinged front wall



