

Der Anhänger ist derzeit nicht verfügbar

AT 4500/22 T-K

Long durability through welded, hot-dip galvanized chasis and tiltable plateau Stability and resilience thanks to 3-sided railing frame Two robust aluminum ramps storable under the loading area Two infinitely adjustable wheel stops Tiltable loading ramp with closed floor, flat drive-up angle and gas-pressure-spring supported lifting aid Optional hydraulic tipping Very versatile High quality, track-adherent chassis Slip- and water-resistant base plate provides high resistance and is replaceable Accessories to customize the trailer available Individual approval in Austria and Germany

* Der AT 4500/22 T-K ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	2.600 kg
Load capacity	1.810 kg
Self-weight	790 kg
Total length	6.215 mm
Total width	2.170 mm
Total height	1.105 mm
Loading dimensions inside - length	4.500 mm
Loading dimensions inside - width	2.010 mm
Loading dimensions inside - height -	
Sill height	650 mm

FURTHER INFORMATION

description	value
Material type	-
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chasis and tiltable plateau Stability and resilience thanks to 3-sided railing frame Two robust aluminum ramps storable under the loading area Two infinitely adjustable wheel stops Tiltable loading ramp with closed floor, flat drive-up angle and gas-pressure-spring supported lifting aid Optional hydraulic tipping Very versatile High quality, track-adherent chassis Slip- and water-resistant base plate provides high resistance and is replaceable Accessories to customize the trailer available Individual approval in Austria and Germany

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Steel fenders
- Multifunctional luminaires
- Torsion-free chassis
- 13-pin light plug
- Supporting wheel
- 2 robust steel ramps
- 2 wheel stops
- Long supports (without threaded spindles)



