

Der Anhänger ist derzeit nicht verfügbar

# AT 4500/22 T-K

Long durability through welded, hot-dip galvanized chasis and tiltable plateau Stability and resilience thanks to 3-sided railing frame Two robust aluminum ramps storable under the loading area Two infinitely adjustable wheel stops Tiltable loading ramp with closed floor, flat drive-up angle and gas-pressure-spring supported lifting aid Optional hydraulic tipping Very versatile High quality, track-adherent chassis Slip- and water-resistant base plate provides high resistance and is replaceable Accessories to customize the trailer available Individual approval in Austria and Germany

\* Der AT 4500/22 T-K ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

## TECHNICAL DETAILS

| description                          | value    |
|--------------------------------------|----------|
| Total weight                         | 3.500 kg |
| Load capacity                        | 2.710 kg |
| Self-weight                          | 790 kg   |
| Total length                         | 6.215 mm |
| Total width                          | 2.170 mm |
| Total height                         | 1.105 mm |
| Loading dimensions inside - length   | 4.500 mm |
| Loading dimensions inside - width    | 2.010 mm |
| Loading dimensions inside - height - |          |
| Sill height                          | 650 mm   |

## FURTHER INFORMATION

| description              | value            |
|--------------------------|------------------|
| Material type            | -                |
| brake                    | decelerated      |
| Single axle / tandem     | Tandem (2 axles) |
| Tires (inches)           | 13 inch          |
| Number of lashing points | 8                |
| Hydraulic system         | No               |
| Hinged front wall        | No               |
| Tilted                   | Yes              |

## PRODUCT DESCRIPTION

Long durability through welded, hot-dip galvanized chasis and tiltable plateau Stability and resilience thanks to 3-sided railing frame Two robust aluminum ramps storable under the loading area Two infinitely adjustable wheel stops Tiltable loading ramp with closed floor, flat drive-up angle and gas-pressure-spring supported lifting aid Optional hydraulic tipping Very versatile High quality, track-adherent chassis Slip- and water-resistant base plate provides high resistance and is replaceable Accessories to customize the trailer available Individual approval in Austria and Germany

## STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Steel fenders
- Multifunctional luminaires
- Torsion-free chassis
- 13-pin light plug
- Supporting wheel
- 2 robust steel ramps
- 2 wheel stops
- Long supports (without threaded spindles)



