

# PKL 300/15 T

Artikelnummer: 24347

## TECHNICAL DETAILS

description	value
Total weight	2.600 kg
Load capacity	1.975 kg
Self-weight	625 kg
Total length	4.450 mm
Total width	2.045 mm
Total height	2.450 mm
Loading dimensions inside - length	3.000 mm
Loading dimensions inside - width	1.515 mm
Loading dimensions inside - height	1.880 mm
Sill height	550 mm

## FURTHER INFORMATION

description	value
Material type	-
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	14 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	No

## PRODUCT DESCRIPTION

Side wall and roof made of 14mm plywood Floor made of 18mm screen printing plate with anti-slip coating Left and right continuous lashing rail with continuously adjustable lashing eyes Stable rear portal and corner profiles Two-winged rear door, secured with espagnolette lock, lockable Ventilation opening Support wheel as standard

## STANDARD EQUIPMENT

- Low loader box trailer
- Platform gates and roof 14mm plywood
- Floor made of 18mm screen printing plate with anti-slip coating
- V-type drawbar
- Ventilation opening left and right
- Rear hinged door with espagnolette lock, lockable
- 8x lashing brackets, infinitely adjustable
- Support wheel as standard

