

Der Anhänger ist derzeit nicht verfügbar



PKL 300/15 T

Side wall and roof made of 14mm plywood Floor made of 18mm screen printing plate with anti-slip coating Left and right continuous lashing rail with continuously adjustable lashing eyes Stable rear portal and corner profiles Two-winged rear door, secured with espagnolette lock, lockable Ventilation opening Support wheel as standard

* Der PKL 300/15 T ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	2.600 kg
Load capacity	1.975 kg
Self-weight	625 kg
Total length	4.450 mm
Total width	2.045 mm
Total height	2.450 mm
Loading dimensions inside - length	3.000 mm
Loading dimensions inside - width	1.515 mm
Loading dimensions inside - height	1.880 mm
Sill height	550 mm

FURTHER INFORMATION

description	value
Material type	-
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	14 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	No

PRODUCT DESCRIPTION

Side wall and roof made of 14mm plywood Floor made of 18mm screen printing plate with anti-slip coating Left and right continuous lashing rail with continuously adjustable lashing eyes Stable rear portal and corner profiles Two-winged rear door, secured with espagnolette lock, lockable Ventilation opening Support wheel as standard

STANDARD EQUIPMENT

- Low loader box trailer
- Platform gates and roof 14mm plywood
- Floor made of 18mm screen printing plate with anti-slip coating
- V-type drawbar
- Ventilation opening left and right
- Rear hinged door with espagnolette lock, lockable
- 8x lashing brackets, infinitely adjustable
- Support wheel as standard

