

Der Anhänger ist derzeit nicht verfügbar

L-AT 400 T-K-2

Long durability through corrosion-resistant, galvanized steel parts Tilttable open loading ramp, flat drive-up angle and gas-pressure-spring supported lifting aid Low own weight, therefore higher load capacity Very versatile High quality, track-adherent chassis smooth running Slip resistant stand rail Easy maintenance and repair on replaceable components Accessories to customize the trailer available Optional closed cargo area (serves as spray protection) through base plate or aluminum checker plate floor (slightly durable)

* Der L-AT 400 T-K-2 ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	2.600 kg
Load capacity	1.970 kg
Self-weight	630 kg
Total length	5.570 mm
Total width	2.080 mm
Total height	615 mm
Loading dimensions inside - length	4.010 mm
Loading dimensions inside - width	2.020 mm
Loading dimensions inside - height -	
Sill height	575 mm

FURTHER INFORMATION

description	value
Material type	-
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	10 inch
Number of lashing points	8
Hydraulic system	No
Hinged front wall	No
Tilted	Yes

PRODUCT DESCRIPTION

Long durability through corrosion-resistant, galvanized steel parts Tilttable open loading ramp, flat drive-up angle and gas-pressure-spring supported lifting aid Low own weight, therefore higher load capacity Very versatile High quality, track-adherent chassis smooth running Slip resistant stand rail Easy maintenance and repair on replaceable components Accessories to customize the trailer available Optional closed cargo area (serves as spray protection) through base plate or aluminum checker plate floor (slightly durable)

STANDARD EQUIPMENT

- Lashing possibilities for securing the load
- Maintenance-free rubber spring axle
- Steel fenders
- Multifunctional luminaires
- Torsion-free chassis of the trailer
- 13-pin light plug
- Supporting wheel
- Ramps storable on loading ramp and slidable across the rear
- 2 wheel stops
- Long supports (without threaded spindles)
- Spare wheel carrier



