

Der Anhänger ist derzeit nicht verfügbar



PMT 300/16 T 3500KG STAHL

Highest durability and long lifespan through the fully welded main frame, a solid and skid-proof steel flooring and the galvanized surface Following sizes are available: 3,0 x 1,6 m or 3,65 x 1,87m Either with a total mass of 3000kg or 3500kg Optional tire dimensions in 13zoll or 14 zoll Individual accessories for the optimal adjustment for your claims: Middle section for loading ramps Bucket support Step treads on left and right side Lockable store box Spare wheel and retainer 4 additional lashing points (2500daN)

* Der PMT 300/16 T 3500kg Stahl ist nach Verfügbarkeit erhältlich ab dem Zentrallager in Oberaich. Bei Lageranhänger ist montiertes Zubehör im Preis nicht inbegriffen, außer es ist explizit in der Produktbeschreibung angeführt. Zubehör wird in alle Länder geliefert.

TECHNICAL DETAILS

description	value
Total weight	3.500 kg
Load capacity	2.739 kg
Self-weight	761 kg
Total length	5.010 mm
Total width	2.203 mm
Total height	1.995 mm
Loading dimensions inside - length	3.020 mm
Loading dimensions inside - width	1.600 mm
Loading dimensions inside - height	260 mm
Sill height	406 mm

FURTHER INFORMATION

description	value
Material type	steel
brake	decelerated
Single axle / tandem	Tandem (2 axles)
Tires (inches)	13 inch
Number of lashing points	6
Hydraulic system	No
Hinged front wall	No
Tilted	No

PRODUCT DESCRIPTION

Highest durability and long lifespan through the fully welded main frame, a solid and skid-proof steel flooring and the galvanized surface Following sizes are available: 3,0 x 1,6 m or 3,65 x 1,87m Either with a total mass of 3000kg or 3500kg Optional tire dimensions in 13zoll or 14 zoll Individual accessories for the optimal adjustment for your claims: Middle section for loading ramps Bucket support Step treads on left and right side Lockable store box Spare wheel and retainer 4 additional lashing points (2500daN)

STANDARD EQUIPMENT

- two ramps with gas spring supported lifting mechanism
- both ramps are stageless shiftable in position and can be adapted to tread with of loaded machine
- solid and skidproof aluminium flooring
- 6 lashing points with a tensile load up to 2500daN
- Accessible mud guards with skidproof coating
- Fully welded and galvanised main frame and sidewalls

